Telefax: +49 2241-3923-90

Telephone: +49 2241-3923-0



Safety Data Sheet

according to Regulation (EC) No 1907/2006

RHEOSEPT-HD universal

Revision date: 20.04.2021 Product code: 29050 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

RHEOSEPT-HD universal

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Alcohol-based hand disinfectant

Uses advised against

Disinfection of mucous membranes and raw wound

1.3. Details of the supplier of the safety data sheet

Company name: NW-Chemie GmbH Street: Langbaurghstr. 15 Place: D-53842 Troisdorf Telephone: +49 2241-3923-0

e-mail: info@rheosol.de

Contact person: Dr. Friedrichs (MSDS qualified

person)

e-mail: sicherheit@rheosol.de
Internet: www.rheosol.de
Responsible Department: Produktsicherheit

1.4. Emergency telephone Giftnotruf Berlin (Germany): +49 30 30686 700

number:

Further Information

This safety data sheet replaces the former safety data sheet.

The affected sections are listed in section 16.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour. Causes serious eye irritation.

May cause drowsiness or dizziness.

Wear protective gloves/ clothes/ goggles/ face protection (section 8) in case of filling of bigger bundel (< 1000

mL).

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:







according to Regulation (EC) No 1907/2006

RHEOSEPT-HD universal

Revision date: 20.04.2021 Product code: 29050 Page 2 of 12

Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use waterspray, foam, CO2, powder to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

Do not spray on a naked flame or any incandescent material. Keep away from sources of

ignition - No smoking. Keep out of the reach of children.

Additional advice on labelling

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Alcohol-water-mixture

Hazardous components

CAS No	Chemical name	Chemical name		
	EC No	Index No	REACH No	
	GHS Classification			
67-63-0	propan-2-ol; isopropyl alcohol; isop	propan-2-ol; isopropyl alcohol; isopropanol		
	200-661-7 01-2119457558-25			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name			
	Specific Conc. Limits, M-factors and ATE				
67-63-0	200-661-7 propan-2-ol; isopropyl alcohol; isopropanol				
	inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg				

Further Information

Note: The danger characteristics refer to the properties of the neat substances.

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.



according to Regulation (EC) No 1907/2006

RHEOSEPT-HD universal

Revision date: 20.04.2021 Product code: 29050 Page 3 of 12

After inhalation

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Provide fresh air.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin irritation persistence, seek medical treatment.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink 1 glass of of water. Seek medical attention if problems persist.

4.2. Most important symptoms and effects, both acute and delayed

No information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Suitable extinguishing media: Water spray jet, Alcohol resistant foam. Extinguishing powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable liquid and vapour. Vapours can form explosive mixtures with air. In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO2).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Do not inhale explosion and combustion gases.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not empty indiluted or in larger quantaties into drains or waters.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13



according to Regulation (EC) No 1907/2006

RHEOSEPT-HD universal

Revision date: 20.04.2021 Product code: 29050 Page 4 of 12

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Further information on handling

Do not eat, drink or smoke at the workplace. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Pyrophoric or self-heating substances. Do not store together with: self-igniting material igniting (oxidating) materials
Material, combustible.
material, flammable.
alkali metals

7.3. Specific end use(s)

No special handling instructions are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance				
DNEL type	DNEL type		Effect	Value	
67-63-0 propan-2-ol; isopropyl alcohol; isopropanol					
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day	
Worker DNEL, long-term		inhalation	systemic	500 mg/m³	
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day	
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day	
Consumer DNI	Consumer DNEL, long-term i		systemic	89 mg/m³	

Print date: 20.04.2021



Safety Data Sheet

according to Regulation (EC) No 1907/2006

RHEOSEPT-HD universal

Revision date: 20.04.2021 Product code: 29050 Page 5 of 12

PNEC values

CAS No	Substance			
Environmen	Environmental compartment			
67-63-0	-63-0 propan-2-ol; isopropyl alcohol; isopropanol			
Freshwater		140,9 mg/l		
Freshwater (intermittent releases)		140,9 mg/l		
Marine water		140,9 mg/l		
Freshwater sediment		552 mg/kg		
Marine sediment		552 mg/kg		
Secondary poisoning		160 mg/kg		
Micro-organisms in sewage treatment plants (STP)		2251 mg/l		
Soil		28 mg/kg		

8.2. Exposure controls







Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Please consider your local regulations

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Do not empty indiluted or in larger quantaties into drains or waters.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: alcoholic

pH-Value: 6,8

Changes in the physical state



according to Regulation (EC) No 1907/2006

DL		CEDI		universal	ı
RГ	IEU	JOEP	טח-ו	universal	н

Revision date: 20.04.2021 Product code: 29050 Page 6 of 12

Melting point: < 0 °C
Boiling point or initial boiling point and 82 °C

boiling range:

Sublimation point: not known
Softening point: not applicable
Pour point: not applicable
Flash point: 22 °C
Sustaining combustion: Not sustaining combustion

Flammability

Solid/liquid: not applicable
Gas: not applicable

Explosive properties

In use, may form flammable / explosive vapour-air mixture.

Lower explosion limits: 2 vol. % Upper explosion limits: 13,4 vol. % Auto-ignition temperature: ca. 400 °C

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties

product not potentially explosive but may form flammable/explosive vapour-air mixtures

Vapour pressure: 43 hPa

(at 20 °C)

Vapour pressure: 229 hPa

(at 50 °C)

Density: 0,875-0,878 g/cm³
Bulk density: not applicable
Water solubility: completely miscible

9.2. Other information

Solid content: not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable liquid and vapour. The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reaction with oxidizing agents.

Reaction with alkali metals.

Reaction with alkaline earth metals.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Alkali metals.

Alkaline earth metals.

Oxidizing agents.



according to Regulation (EC) No 1907/2006

RHEOSEPT-HD universal

Revision date: 20.04.2021 Product code: 29050 Page 7 of 12

Strong acid.

10.6. Hazardous decomposition products

Prolonged exposure to direct and intenisve sunlight may form explosive peroxides in the product

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

For oral intoxication by isopropanol of humans several symptoms are known: sickness, vomitus, stomach ache, gastritis, Reduction of blood pressure, bodytemperature drop, coma, respiratory paralysis. 0,5 L of 70% V/V Isopropanol mixture may be lethal. Source: GESTIS substance data base of the BG Institute for Occupational Safety and IFA.

CAS No	Chemical name	Chemical name					
	Exposure route	Dose		Species	Source		Method
67-63-0	propan-2-ol; isopropyl ald	cohol; isopro	opanol				
	oral	LD50 mg/kg	>2000	Rat			
	dermal	LD50 mg/kg	>2000	Rabbit			
	inhalation (4 h) vapour	LC50	30 mg/l				_

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Irritantant effect on the eye: irritant A skin-irritating effect of isopropanol occurs with volunteers only with prior superficial injury (abrasion) or after prior 10 min. storing in water. Source: GESTIS substance data base of the BG Institute for Occupational Safety and IFA

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Practical experience

No data available.

11.2. Information on other hazards

Other information

May cause drowsiness or dizziness.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

RHEOSEPT-HD universal

Revision date: 20.04.2021 Product code: 29050 Page 8 of 12

CAS No	Chemical name	Chemical name					
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alc	ohol; isoprop	anol				
	Acute fish toxicity	LC50 mg/l	>100	96 h	Leuciscus idus		
	Acute algae toxicity	ErC50 mg/l	>1000		Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	13299	48 h	Daphnia magna		

12.2. Persistence and degradability

Easily biodegradable.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	Biological degradability	53 %	5	
	Readily biodegradable.		•	

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.7. Other adverse effects

There are no data available on the mixture itself.

Further information

Avoid release to the environment. Do not empty indiluted or in larger quantaties into drains or waters.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Recycle / dispose of observing national, regional, state, provincial and local health, safety & pollution laws. If questions exist, contact the appropriate agencies.

List of Wastes Code - residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother

liquors; hazardous waste

List of Wastes Code - used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother

liquors; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.



according to Regulation (EC) No 1907/2006

RHEOSEPT-HD universal

Revision date: 20.04.2021 Product code: 29050 Page 9 of 12

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity:

Excepted quantity:

E2

EmS:

F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)



according to Regulation (EC) No 1907/2006

RHEOSEPT-HD universal Revision date: 20.04.2021 Product code: 29050 Page 10 of 12

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A180

1 L

Y341

Excepted quantity:

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No special handling instructions are necessary.

14.7. Maritime transport in bulk according to IMO instruments

Not classified for this transport carrier.

Other applicable information

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): 63,1 % (552,945 g/l)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: propan-2-ol; isopropyl alcohol; isopropanol

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,10,11,12,13,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage

of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the



according to Regulation (EC) No 1907/2006

RHEOSEPT-HD universal

Revision date: 20.04.2021 Product code: 29050 Page 11 of 12

International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

P: Marine Pollutant

GHS: Globally Harmonized System of Classification and Labelling of Chemicals CLP: Classification, Labelling and Packaging (Regulation (EC) No. 1272/2008) EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Further Information

Follow the instructions for use on the label.



according to Regulation (EC) No 1907/2006

RHEOSEPT-HD universal

Revision date: 20.04.2021 Product code: 29050 Page 12 of 12

@1604.B160022

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)